

PANTHER 6x6 electric

Aircraft Rescue and Fire Fighting Vehicle 11,000/1,370/250



Base specification

▪ Chassis:

- › Rosenbauer 40.980 6x6
- › Gearbox: CDT 3-speed automatic transmission
- › Brakes: Electronic Brake System with disc brakes (incl. regenerative braking)

▪ Drive System:

- › All-Electric drive with Energy Backup System
- › High Voltage System with four electric motors powered by HV-Battery (nominal: 256 kWh)
- › ICAO Attack (Doc 9137, 2.7 response time) compliant in pure electric operation
- › Energy Backup System (EBU) powered by diesel engine (235 kW)
- › Power:
 - Pure electric: 720 kW (980 HP)
 - Combined (RIV/Boost): 880 kW (1200 HP)
- › Acceleration:
 - Pure electric: 0 - 80 km/h < 25 sec
 - Combined (RIV/Boost): 0 - 80 km/h < 20 sec
- › Maximum speed: 120 km/h
- › Combined charging system CCS-Type 2:
 - AC: 1x up to 22 kW
 - DC: 2x up to 150 kW (up to 300 kW total)

▪ Driving compartment:

- › Crew: 1 + 3
- › Rosenbauer panorama view - safety cab, certified according to ECE R29-3, hinged doors with manually sliding windows, tiltable center console

▪ Vehicle body:

- › Modular body concept consisting of laser-cut, bent aluminum sheets and plastic linings
- › Polypropylene wet side water- / foamtank

▪ Extinguishing agent tank:

- › Water tank capacity: 11,000 l
- › Foam tank capacity: 1,370 l
- › Powder capacity: 250 kg

▪ Pump unit:

- › Type: Rosenbauer N80 (light alloy)
- › Output: up to 9,000 l/min at 12 bar
- › Pump-drive:
 - Pure electric or Combined (EBU-assisted)

▪ Proportioning system:

- › Type: Rosenbauer FIXMIX 2.0 E
- › Proportioning ratio: 1%, 3%, 6%

PANTHER 6x6 electric

Aircraft Rescue and Fire Fighting Vehicle 11,000/1,370/250



▪ HRET:

- › Rosenbauer STINGER 54 with RM65 C and piercing tool
- › Output: up to 6,000 l/min (stowed)
up to 3,800 l/min (raised)
up to 1,000 l/min (piercing tool)

▪ Bumper turret:

- › Rosenbauer RM 15
- › Output: up to 2,000 l/min

▪ Quick attack:

- › Rosenbauer water/foam hose reel 30m, DN32
- › Powder hose reel 30m, DN32

▪ Options:

- › Tire Pressure Measuring System
- › ESC (Electronic Stability Control)
- › Rear axle Steering (electro-hydraulic)
- › Power supply unit (230/400 V) 6 kVA or 18 kVA
- › Light mast Flexilight 8x LED
- › Airfield search lights
- › Exterior Water/Foam tank level indicator
- › Birdview camera system
- › RDS Connected Fleet (telematic system)

Product number PA146-9701

Dimensions and weight

L x W x H	11,770 x 3,000 x 3,800 mm
Permissible total weight	40,500 kg



symbolic image



symbolic image



symbolic image



symbolic image

Contact

Rosenbauer International AG
Paschinger Straße 90
4060 Leonding, Austria
Tel.: +43 732 6794-0
Fax: +43 732 6794-91

www.rosenbauer.com

Follow us on      

Text and images non-binding. The images may depict special editions that are only available at an additional charge.
Subject to change due to technical advances.

Vers. 1.0
SCle_2024-10-01